

## TECHNICAL SPECIFICATION

Product	DA220LTE	DA240LTE	DA260LTE	DA280LTE	DA2120LTE	DA2160LTE
INPUTS	2	2	2	2	2	2
OUTPUTS	2	4	6	8	12	16
FREQUENCY RANGE	45-230/470-790MHz	45-230/470-790MHz	45-230/470-790MHz	45-230/470-790MHz	45-230/470-790MHz	45-230/470-790MHz
GAIN	10dB+2	10dB+2	10dB+2	10dB+2	10dB+2	10dB+2
NOISE MAX	>3.5dB	>3.5dB	>3.5dB	>3.5dB	>3.5dB	>3.5dB
MAX OUTPUT	78dB	78dB	78dB	78dB	78dB	78dB
ISOLATION BETWEEN PORTS	>20dB	>20dB	>20dB	>20dB	>20dB	>20dB
RETURN PATH FREQUENCY	5-30MHz	5-30MHz	5-30MHz	5-30MHz	5-30MHz	5-30MHz
IMPEDANCE	75ohm	75ohm	75ohm	75ohm	75ohm	75ohm
CONNECTIONS	F-type	F-type	F-type	F-type	F-type	F-type
MAINS POWER	230V AC ± 10% 50Hz Fitted Mains Plug BS1363 3A rating					