



Technology..since 1937
www.antiference.co.uk



Standard HDMI Cables with Ethernet

- Standard HDMI cables
- High speed with Ethernet (lengths 0.5m-5m)
- Standard speed with Ethernet (lengths 7.5m-20m)
- Supports resolutions up to 2160p@60 4:4:4 with HDCP2.2
- 18Gbps bandwidth
- 0.5m - 20m lengths
- Gold plated connectors
- Supports HDR, HDR10, HDR10+, Dolby Vision, HLG



Technical Specification	
Audio/Video	
HDMI Compliance	HDMI 1.4 (backwards compatible with HDMI 1.1)
HDCP Compliance	HDCP 1.4, 2.2
Video Bandwidth	18Gbps
Video Resolution	4K@60Hz, 1080p, 720p RGB/YCBCR 4:4:4
Transmission Distance	0.5m, 1m, 1.5m, 3m, 5m, 7.5m, 10m, 15m, 20m
Colour Space	RGB 4:4:4, YCbCr 4:4:4, YCbCr 4:2:2, YCbCr 4:2:0
Colour Depth	8/10/12 bit
Supported Formats	3D, ARC, EARC, HEC, HDR, HDR10, HDR10+, Dolby Vision, HLG
Audio Formats	LPCM 2.0/2.1/5.1/6.1/7.1, Dolby Digital, Dolby TrueHD, Dolby Digital Plus (DD+) & Dolby Atmos
Mechanical	
Cable Jacket	PVC
Connectors	HDMI A Gold Plated
Colour	Black
Outside Diameter	0.5M - 6mm
	1M - 6mm
	1.5M - 6mm
	3M - 6mm
	5M - 6mm
	7.5M - 6mm
	10M - 7.3mm
Cable Gauge	15M - 8mm
	20M - 8mm
	0.5M - 30AWG
	1M - 30AWG
	1.5M - 30AWG
	3M - 30AWG
	5M - 30AWG
Operating Temperature	7.5M - 30AWG
	10M - 28AWG
	15M - 26AWG
	20M - 26AWG
Storage Temperature	0°C to 50°C (32°F to 122°F)
Relative Humidity	-40°C to 70°C (-8°F to 158°F)
	75%

